



Certificate number: 2301743 (1)

Issued 25/01/2023

Expires 25/01/2028

## Kiwa Regulation 4 (KUKreg4) Certification

Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a)

Model number(s) – see Appendix

### Grohe AG.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

**Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009 Northern Ireland and 2014 Byelaws Scotland.**

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

David Jay, Business Unit Manager – Authorised Signatory  
Kiwa Watertec

Publication of this certificate is allowed.

Products are intended to be used in the UK only. For other countries, other (National) requirements will apply.

See <https://www.kiwa.com/gb/en/about-kiwa/water-products/> or the QR code below to ensure that the certificate is still valid.

Kiwa Watertec  
(A Trading Division of Kiwa Ltd)  
26A Rassau Industrial Estate  
Ebbw Vale  
Gwent  
NP23 5SD  
United Kingdom  
T +44 (0)1495 308185  
[uk.water@kiwa.com](mailto:uk.water@kiwa.com)  
[www.kiwa.co.uk](http://www.kiwa.co.uk)

**Certificate Issued to:**  
Grohe AG  
Industriepark Edelburg  
58675 Hemer  
Germany



# Product Certificate

Appendix to Certificate number: 2301743

---

The following products belong to this certificate

|                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>PRODUCT DESCRIPTION</b><br>Range of single hole, single outlet, fixed, electronically controlled tap assemblies with brass bodies (chrome plated), The flow is controlled by a solenoid valve activated via an infra-red sensor. The spout outlet incorporates a plastic aerator.<br><br>ATS3 – Without Production Surveillance.                                                                                                              |
| <b>MODEL(S)</b><br>36.421;<br>36.422.                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>SIZE:</b><br>Stainless steel braided PEX lined flexible hose assemblies incorporating 3/8" captive nut end connection.                                                                                                                                                                                                                                                                                                                        |
| <b>SCOPE:</b><br>Manufacturer recommended maximum working pressure 10 Bar & maximum operating temperature 60°C.<br>Hygienic Purposes: Non-metallic materials suitable for continuous use up to 60°C.                                                                                                                                                                                                                                             |
| <b>MARKING</b><br>Grohe on body.                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>MATERIALS</b><br>Non-metallic materials assessed (BS6920) to point of discharge.                                                                                                                                                                                                                                                                                                                                                              |
| <b>BACKFLOW PROTECTION NOTES</b><br>If this tap or combination tap is installed so that its base is no lower than the spillover level of the receiving vessel (for example, a sink or washbasin), a Type AUK3 air gap is achieved which permits installation of the tap in any premises where backflow protection up to Fluid Category 5 is required at the tap.<br>Consider balanced supplies or appropriate backflow protection at the inlets. |
| <b>ADDITIONAL NOTES</b><br>Opacity cannot be guaranteed at inlet hoses.                                                                                                                                                                                                                                                                                                                                                                          |

## Extra Notes