



Certificate number: 2210780 (1)

Issued 25/10/2022

Expires 25/10/2027

Kiwa Regulation 4 (KUKreg4) Certification

Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a)

Model number(s) – see Appendix

Grohe AG.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009 Northern Ireland and 2014 Byelaws Scotland.

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

David Jay, Business Unit Manager – Authorised Signatory
Kiwa Watertec

Publication of this certificate is allowed.

Products are intended to be used in the UK only. For other countries, other (National) requirements will apply.

See <https://www.kiwa.com/gb/en/about-kiwa/water-products/> to ensure that the certificate is still valid.

CERTIFICATE

Kiwa Watertec
(A Trading Division of Kiwa Ltd)
26A Rassau Industrial Estate
Ebbw Vale
Gwent
NP23 5SD
United Kingdom
T +44 (0)1495 308185
uk.water@kiwa.com
www.kiwa.co.uk

Certificate Issued to:
Grohe AG
Industreipark Edelburg
58675 Hemer
Germany



Product Certificate

Appendix to Certificate number: 2210780

The following products belong to this certificate

PRODUCT DESCRIPTION Range of wall mounted concealed thermostatic blending valves with plastic bodies (various finished face plates). The flow is controlled by a ceramic disc diverter headworks with a cube type operating member. The temperature is controlled by a thermostatic cartridge with dome type operating members incorporating a manual override button. Both inlets incorporate an approved check valve cartridge, however, the complete product has not been fully tested to demonstrate it provides backflow protection. ATS3 – Without Production Surveillance.
MODEL(S) Grotherm Cube range: 24155000 – Chrome Plated; 24155AL0 – Brushed Hard Graphite; 24155DC0 – Supersteel.
SIZE: 24mm Ø.
SCOPE: Manufacturer recommended maximum working pressure 6 Bar & maximum operating temperature 60°C. Hygienic Purposes: Non-metallic materials suitable for continuous use up to 60°C.
MARKING Grohe on housing.
MATERIALS Non-metallic materials assessed (BS6920) to point of discharge.
BACKFLOW PROTECTION NOTES Consider balanced supplies or appropriate backflow protection at the inlets.
ADDITIONAL NOTES All water contact & exposed components satisfy opacity requirements.

Extra Notes