



Certificate number: 2304732 (1)

Issued 13/06/2023

Expires 13/06/2028

Kiwa Regulation 4 (KUKreg4) Certification

Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a)

Model number(s) – see Appendix

Grohe AG.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009 Northern Ireland and 2014 Byelaws Scotland.

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

David Jay, Business Unit Manager – Authorised Signatory
Kiwa Watertec

Publication of this certificate is allowed.

Products are intended to be used in the UK only. For other countries, other (National) requirements will apply.

See <https://www.kiwa.com/gb/en/about-kiwa/water-products/> or the QR code below to ensure that the certificate is still valid.

Kiwa Watertec
(A Trading Division of Kiwa Ltd)
26A Rassau Industrial Estate
Ebbw Vale
Gwent
NP23 5SD
United Kingdom
T +44 (0)1495 308185
uk.water@kiwa.com
www.kiwa.co.uk

Certificate Issued to:
Grohe AG
Industriepark Edelburg
58675 Hemer
Germany



Product Certificate

Appendix to Certificate number: 2304732

The following products belong to this certificate

PRODUCT DESCRIPTION Single hole, single outlet (swivel) combination tap assembly with brass body (chrome plated), incorporating ceramic cartridge headwork and single lever operating member. Spout outlet incorporates a plastic aerator ATS3 – Without Production Surveillance.
MODEL(S) Minta range: 32.917.xxx 32.488.xxx Where xxx denotes finish, can be replaced by: 000 – Chrome DC0 – Supersteel DL0 – Brushed warm sunset DA0 – Warm sunset AL0 – Brushed hard graphite A00 – Hard graphite KS0 – Velvet black
SIZE: Stainless steel braided PEX lined flexible hose assemblies incorporating 3/8 BSP captive nut.
SCOPE: Manufacturer recommended maximum working pressure 10 Bar & maximum operating temperature 70°C. Hygienic Purposes: Non-metallic materials suitable for continuous use up to 70°C.
MARKING Grohe on body.
MATERIALS Non-metallic materials assessed (BS6920) to point of discharge/to backflow prevention device.
BACKFLOW PROTECTION NOTES Consider balanced supplies or appropriate backflow protection at the inlets. If this tap or combination tap is installed so that its base is no lower than the spillover level of the receiving vessel (for example, a sink or washbasin), a Type AUK3 air gap is achieved which permits installation of the tap in any premises where backflow protection up to Fluid Category 5 is required at the tap.
ADDITIONAL NOTES Opacity cannot be guaranteed at inlet connections/hoses.

Extra Notes