



Certificate number: 2307736 (1)

Issued 25/07/2023

Expires 25/07/2028

## Kiwa Regulation 4 (KUKreg4) Certification

Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a)

Model number(s) – see Appendix

### Grohe AG.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

**Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009 Northern Ireland and 2014 Byelaws Scotland.**

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

David Jay, Business Unit Manager – Authorised Signatory  
Kiwa Watertec

Publication of this certificate is allowed.

Products are intended to be used in the UK only. For other countries, other (National) requirements will apply.

See <https://www.kiwa.com/gb/en/about-kiwa/water-products/> or the QR code below to ensure that the certificate is still valid.

Kiwa Watertec  
(A Trading Division of Kiwa Ltd)  
26A Rassau Industrial Estate  
Ebbw Vale  
Gwent  
NP23 5SD  
United Kingdom  
T +44 (0)1495 308185  
[uk.water@kiwa.com](mailto:uk.water@kiwa.com)  
[www.kiwa.co.uk](http://www.kiwa.co.uk)

**Certificate Issued to:**  
Grohe AG  
Industriepark Edelburg  
58675 Hemer  
Germany



# Product Certificate

Appendix to Certificate number: 2307736

The following products belong to this certificate

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>PRODUCT DESCRIPTION</b><br>Range of wall mounted, two-hole, single outlet (fixed) combination tap assembly (chrome plated brass body) incorporating a ceramic cartridge headwork with a single lever operating member and self-cancelling diverter to shower outlet. The shower outlet incorporates an approved check valve cartridge, however, the complete product has not been fully tested to demonstrate it provides backflow protection. The spout outlet incorporates a plastic aerator.<br>ATS3 – Without Production Surveillance. |
| <b>MODEL(S)</b><br>33553003, 33553AL3 & 33553DC3.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>SIZE:</b><br>$\frac{3}{4}$ " BSP(M) x $\frac{1}{2}$ " BSP (M) Offset unions.                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>SCOPE:</b><br>Manufacturer recommended maximum working pressure 10 Bar & maximum operating temperature 60°C.<br>Hygienic Purposes: Non-metallic materials suitable for continuous use up to 60°C.                                                                                                                                                                                                                                                                                                                                          |
| <b>MARKING</b><br>Grohe on body.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>MATERIALS</b><br>Non-metallic materials assessed (BS6920) to point of discharge.                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>BACKFLOW PROTECTION NOTES</b><br>Consider balanced supplies or appropriate backflow protection at the inlets.<br>Consideration must be made on installation to the airgap arrangement.                                                                                                                                                                                                                                                                                                                                                     |
| <b>ADDITIONAL NOTES</b><br>All water contact & exposed components satisfy opacity requirements.                                                                                                                                                                                                                                                                                                                                                                                                                                               |

Extra Notes