



Certificate number: 2307737 (1)

Issued 25/07/2023

Expires 25/07/2028

Kiwa Regulation 4 (KUKreg4) Certification

Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a)

Model number(s) – see Appendix

Grohe AG.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009 Northern Ireland and 2014 Byelaws Scotland.

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

David Jay, Business Unit Manager – Authorised Signatory
Kiwa Watertec

Publication of this certificate is allowed.

Products are intended to be used in the UK only. For other countries, other (National) requirements will apply.

See <https://www.kiwa.com/gb/en/about-kiwa/water-products/> or the QR code below to ensure that the certificate is still valid.

Kiwa Watertec
(A Trading Division of Kiwa Ltd)
26A Rassau Industrial Estate
Ebbw Vale
Gwent
NP23 5SD
United Kingdom
T +44 (0)1495 308185
uk.water@kiwa.com
www.kiwa.co.uk

Certificate Issued to:
Grohe AG
Industriepark Edelburg
58675 Hemer
Germany



KUKreg4

Product Certificate

Appendix to Certificate number: 2307737

The following products belong to this certificate

PRODUCT DESCRIPTION 'Grohe Essence' range of four hole, single outlet (fixed) combination tap assemblies with brass bodies (various finishes), incorporating a ceramic cartridge headwork with single lever operating members and a self-cancelling diverter to shower outlet. The connection to shower outlet incorporates a single check valve cartridge, verified by test (suitable for backflow prevention against Fluid Category 2). The spout outlet incorporates a plastic aerator, and the product is also supplied with a shower hose, shower handset and metal backnuts. ATS3 – Without Production Surveillance.
MODEL(S) 19.578.XX1 Essence.
SIZE: Stainless steel braided PEX lined flexible hose assemblies incorporating ½" captive nut end connections.
SCOPE: Manufacturer recommended maximum working pressure 10 Bar & maximum operating temperature 60°C. Hygienic Purposes: Non-metallic materials suitable for continuous use up to 60°C.
MARKING Grohe on spout & shower outlet.
MATERIALS Non-metallic materials assessed (BS6920) to point of discharge.
BACKFLOW PROTECTION NOTES Consider balanced supplies or appropriate backflow protection at the inlets. Consideration must be made on installation to the airgap arrangement.
ADDITIONAL NOTES Opacity cannot be guaranteed at inlet connections/hoses. Connecting hoses to be installed where light is excluded.

Extra Notes