



Certificate number: 2304745 (1)

Issued 25/04/2023

Expires 25/04/2028

Kiwa Regulation 4 (KUKreg4) Certification

Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a)

Model number(s) – see Appendix

Grohe AG.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009 Northern Ireland and 2014 Byelaws Scotland.

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

David Jay, Business Unit Manager – Authorised Signatory
Kiwa Watertec

Publication of this certificate is allowed.

Products are intended to be used in the UK only. For other countries, other (National) requirements will apply.

See <https://www.kiwa.com/gb/en/about-kiwa/water-products/> or the QR code below to ensure that the certificate is still valid.

Kiwa Watertec
(A Trading Division of Kiwa Ltd)
26A Rassau Industrial Estate
Ebbw Vale
Gwent
NP23 5SD
United Kingdom
T +44 (0)1495 308185
uk.water@kiwa.com
www.kiwa.co.uk

Certificate Issued to:
Grohe AG
Industriepark Edelburg
58675 Hemer
Germany



Product Certificate

Appendix to Certificate number: 2304745

The following products belong to this certificate

PRODUCT DESCRIPTION Single hole, single outlet (fixed) combination tap assembly with brass body (various finishes), incorporating ceramic cartridge headwork and single lever operating member. Spout outlet incorporates a plastic aerator and models are supplied with a pop-up waste.
ATS3 – Without Production Surveillance.
MODEL(S) Essence range: 24 171 001 – Chrome 24 171 A01 – Hard graphite 24 171 AL1 – Brushed hard graphite 24 171 BE1 – Polished nickel 24 171 DA1 – Warm sunset 24 171 DC1 – Supersteel 24 171 DL1 – Brushed warm sunset 24 171 EN1 – Brushed nickel 24 171 GL1 – Cool sunrise 24 171 GN1 – Brushed cool sunrise 24 172 001 – Chrome 24 172 A01 – Hard graphite 24 172 AL1 – Brushed hard graphite 24 172 BE1 – Polished nickel 24 172 DA1 – Warm sunset 24 172 DC1 – Supersteel 24 172 DL1 – Brushed warm sunset 24 172 EN1 – Brushed nickel 24 172 GL1 – Cool sunrise 24 172 GN1 – Brushed cool sunrise
SIZE: Stainless steel braided PEX lined flexible hose assemblies incorporating 3/8 BSP captive nut.
SCOPE: Manufacturer recommended maximum working pressure 10 Bar & maximum operating temperature 60°C. Hygienic Purposes: Non-metallic materials suitable for continuous use up to 60°C.
MARKING Grohe on body.
MATERIALS Non-metallic materials assessed (BS6920) to point of discharge.
BACKFLOW PROTECTION NOTES If this tap or combination tap is installed so that its base is no lower than the spillover level of the receiving vessel (for example, a sink or washbasin), a Type AUK3 air gap is achieved which permits installation of the tap in any premises where backflow protection up to Fluid Category 5 is required at the tap. Consider balanced supplies or appropriate backflow protection at the inlets.
ADDITIONAL NOTES Opacity cannot be guaranteed at inlet connections/hoses

Extra Notes