

Product certificate K6187-8



Valid from 2026-04-01

Replaces

K6187/07

Page

1 of 3

Connecting valves

STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Certification, Kiwa declares that legitimate confidence exists that the products supplied by

Grohe AG

as specified in this product certificate and marked with the Kiwa®-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with Kiwa evaluation guideline BRL K604:2023 "Stop- and connecting cocks" dated 2022-01-07.

Wim van Loon
Managing Director Nederland

Publication of this certificate is allowed.

Advice: consult www.kiwa.com in order to ensure that this certificate is still valid.



Kiwa Nederland B.V.
Sir Winston Churchilllaan 273
P.O. Box 70
2280 AB RIJSWIJK
The Netherlands
Tel. +31 88 998 44 00
NL.Kiwa.Info@kiwa.com
www.kiwa.com

Grohe AG
Industriepark Edelburg
58675 HEMER
Germany
Tel. (+49) 2372 930
info@grohe.com
www.grohe.com

K6187-8**Connecting valves****PRODUCT SPECIFICATION**

The products mentioned below belong to this product certificate:

Article number	Dimensions	Description
22.018.000	G1/2" x G3/8"	standard handle, metal escutch.
22.018.00M	G1/2" x G3/8"	standard handle, metal escutch.
22.019.000	G1/2" x G3/8"	standard handle
22.023.000	G1/2" x G3/8"	standard handle, metal escutch., self-sealing
22.023.00M	G1/2" x G3/8"	standard handle, metal escutch., self-sealing
22.024.000	G1/2" x G3/8"	standard handle, self-sealing
22.025.00M	G1/2" x G1/2"	standard handle, metal escutch.
22.026.000	G1/2" x G1/2"	standard handle
22.027.00M	G1/2" x G1/2"	standard handle, metal escutch., self-sealing
22.028.000	G1/2" x G1/2"	standard handle, self-sealing
22.029.000	G1/2" x G3/8"	standard handle, metal escutch.
22.031.000	G1/2" x G3/8"	standard handle, metal escutch., self-sealing
22.032.000	G1/2" x G1/2"	standard handle, metal escutch.
22.037.000	G1/2" x G3/8"	metal handle, metal escutch.
22.038.000	G1/2" x G3/8"	metal handle
22.039.000	G1/2" x G3/8"	metal handle, metal escutch., self-sealing
22.040.000	G1/2" x G3/8"	metal handle, self-sealing
22.041.000	G1/2" x G1/2"	metal handle, metal escutch.
22.042.000	G1/2" x G1/2"	metal handle
22.043.000	G1/2" x G1/2"	metal handle, metal escutch., self-sealing
22.044.000	G1/2" x G1/2"	metal handle, self-sealing
22.045.000	G1/2" x G3/8"	metal handle, metal escutch.
22.047.00M	G1/2" x G3/8", cap	standard handle, metal escutch.
22.046.000	G1/2" x G1/2"	metal handle, metal escutch.
22.048.00M	G1/2" x G3/8", cap	standard handle, metal escutch., self-sealing
22.049.000	G1/2" x G3/8", cap	metal handle, metal escutch.
22.051.000	G1/2" x G3/8", cap	metal handle, metal escutch., self-sealing
22.052.000	G3/8" x G3/8"	standard handle, metal escutch., self-sealing
22.053.000	G3/8" x G3/8"	standard handle, metal escutch.
490405045	G3/8"x R1/2"	PA water connection valve
429789999P	G3/8"x R1/2"	PA water connection valve

Connecting valves

Fitness for contact with drinking water

These products are approved on the basis of the requirements for hygienic aspects set in the "Regeling materialen en chemicaliën drink- en warm tapwatervoorziening" ("Materials and chemicals in the supply of drinking water and warm tap water Regulation" dated 01-07-2017; published in the Government Gazette).

These hygienic aspects are based on two main criteria. The product shall permanently comply with:

- The product recipe approved during the assessment procedure. This recipe is not to be changed without prior approval by Kiwa according to the Kiwa approval procedure for the hygienic aspects;
- Specific product requirements for the hygienic aspects.

The recipe and specific product requirements are laid down in the for confidentiality reasons undisclosed 'appendix hygienic aspects' to this certificate.

MARKING

The Kiwa®-mark products are marked with the word mark "KIWA  or .

Place of the mark:

- On the body

Compulsory specifications:

- Manufacturers name Grohe, on the body;
- Nominal size: "DN", on the body and compression fitting (if applicable).

Method of marking:

- Non-erasable;
- visible after assembly.

APPLICATION AND USE

Connecting valves are intended to be used in drinking water installations with a maximum operating pressure of 1000 kPa and a water temperature of maximum 90 °C. The recommended limits for correct use are a maximum operating pressure of 500 kPa and a water temperature of maximum 65 °C.

RECOMMENDATIONS FOR THE CUSTOMERS

Check at the time of delivery whether:

- The supplier has delivered in accordance with the agreement;
- The mark and the marking method are correct;
- The products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

- Grohe AG
- and, if necessary,
- Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.