



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

## Essential Glue

Material number 40915000/40916000

Revision date: 12/9/2017

Version: 3

Language: en-CA,US

Date of print: 12/10/2017

Page: 1 of 9

## 1. Product and company identification

### Product identifier

Trade name: Essential Glue  
This safety data sheet pertains to the following products:  
40915000  
40916000

### Relevant identified uses of the substance or mixture and uses advised against

General use: Adhesive

### Details of the supplier of the safety data sheet

Company name: Grohe AG  
Street/POB-No.: Industriepark Edelburg  
Postal Code, city: 58675 Hemer  
Germany  
WWW: www.grohe.com  
E-mail: info@grohe.com  
Telephone: +49 (0)2372 93-0  
Telefax: +49 (0)2372 93-1322  
Dept. responsible for information:  
Telephone: +49 (0)2372 93-2037  
sustainability@grohe.com

### Emergency phone number

**GIZ-Nord, Göttingen, Germany,  
Telephone: +49 551-19240**

## 2. Hazards identification

### Emergency overview

Appearance: Physical state at 20 °C and 101.3 kPa: solid  
Form: pasty  
Color: white  
Odor: characteristic  
Classification: This material is classified as not hazardous.

### Regulatory status

This material is not considered hazardous by the U.S. OSHA Hazard Communication Standard (29 CFR 1910.1200) and SIMDUT in Canada.

### Hazards not otherwise classified

Special danger of slipping by leaking/spilling product.  
see section 11: Toxicological information

## 3. Composition / Information on ingredients

Chemical characterisation: Mixture of the substances listed below with non-hazardous additions



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

## Essential Glue

Material number 40915000/40916000

Revision date: 12/9/2017

Version: 3

Language: en-CA,US

Date of print: 12/10/2017

Page: 2 of 9

Relevant ingredients:

CAS No.	Designation	Content	Classification
CAS 2768-02-7	Trimethoxyvinylsilane	< 3 %	Flammable Liquid 3. Acute Toxicity 4 (inhalative).
CAS 52829-07-9	Bis(2,2,6,6-Tetramethyl-4-piperidyl)sebacate	< 1 %	Eye Damage 1. Aquatic toxicity - acute 1. Aquatic toxicity - chronic 2.

Additional information: Contains: Calcium carbonate, Titanium dioxide, Silicon dioxide, Aluminium oxide: The maximum workplace exposure limits are, where necessary, listed in section 8.

### 4. First aid measures

In case of inhalation: Move victim to fresh air. Seek medical treatment in case of troubles.

Following skin contact: Immediately clean with water and soap followed by thorough rinsing. Take off contaminated clothing and wash it before reuse. In case of skin reactions, consult a physician.

After eye contact: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

After swallowing: Rinse mouth. Never give anything by mouth to an unconscious person. Do not induce vomiting. Consult doctor afterwards.

#### Most important symptoms and effects, both acute and delayed

No data available

#### Information to physician

Treat symptomatically.

### 5. Fire fighting measures

Flash point/flash point range: Not applicable

Auto-ignition temperature: No data available

Suitable extinguishing media: Water fog, foam, extinguishing powder, carbon dioxide.

Extinguishing media which must not be used for safety reasons: Full water jet

#### Specific hazards arising from the chemical

May form dangerous gases and vapours in case of fire.  
In case of fire may be liberated: nitrogen oxides (NO<sub>x</sub>), carbon monoxide and carbon dioxide

Protective equipment and precautions for firefighters: Wear self-contained positive pressure breathing apparatus and full firefighting protective clothing.

Additional information: Do not allow water used to extinguish fire to enter drains, ground or waterways.



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

## Essential Glue

Material number 40915000/40916000

Revision date: 12/9/2017

Version: 3

Language: en-CA,US

Date of print: 12/10/2017

Page: 3 of 9

## 6. Accidental release measures

- Personal precautions: Provide adequate ventilation. Avoid contact with the substance. Do not breathe mist/vapors/spray. Avoid contact with skin and eyes. Wear appropriate protective equipment. Take off contaminated clothing and wash it before reuse.
- Environmental precautions: Do not allow to enter into ground-water, surface water or drains.
- Methods for clean-up: Take up mechanically, placing in appropriate containers for disposal. Thoroughly clean surrounding area.
- Additional information: Special danger of slipping by leaking/spilling product.

## 7. Handling and storage

### Handling

Advices on safe handling: Provide adequate ventilation, and local exhaust as needed. Avoid contact with the substance. Do not breathe mist/vapors/spray. Avoid contact with skin and eyes. Wear appropriate protective equipment. Take off contaminated clothing and wash it before reuse. Do not eat, drink or smoke when using this product. Wash hands before breaks and after work.

### Storage

Requirements for storerooms and containers:

Storage temperature: 5 °C up to 25 °C.

Protect from frost. Protect from heat and direct sunlight.

Keep container tightly closed in a cool, well-ventilated place.

Hints on joint storage: Do not store together with food.



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

## Essential Glue

Material number 40915000/40916000

Revision date: 12/9/2017

Version: 3

Language: en-CA,US

Date of print: 12/10/2017

Page: 4 of 9

## 8. Exposure controls / personal protection

### Exposure guidelines

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
471-34-1	Calcium carbonate	Canada, Alberta: OEL 8 hour	10 mg/m <sup>3</sup>
		Canada, BC: OEL STEL	20 mg/m <sup>3</sup> (Calcium carbonate incl. Limestone, Marble)
		Canada, BC: OEL TWA	10 mg/m <sup>3</sup> (Calcium carbonate incl. Limestone, Marble)
		Canada, Québec: VEMP	10 mg/m <sup>3</sup> (inhalable fraction)
		USA: NIOSH: TWA	10 mg/m <sup>3</sup> (inhalable fraction)
		USA: NIOSH: TWA	5 mg/m <sup>3</sup> (respirable fraction)
13463-67-7	Titanium dioxide	Canada, Alberta: OEL 8 hour	10 mg/m <sup>3</sup>
		Canada, BC: OEL TWA	10 mg/m <sup>3</sup>
		Canada, BC: OEL TWA	3 mg/m <sup>3</sup> respirable fraction
		Canada, Québec: VEMP	10 mg/m <sup>3</sup> (inhalable fraction)
		USA: ACGIH: TWA	10 mg/m <sup>3</sup>
		USA: OSHA: TWA	15 mg/m <sup>3</sup>
2768-02-7	Trimethoxyvinylsilane	Canada, Ontario: OEL STEL	60 mg/m <sup>3</sup> ; 10 ppm
7631-86-9	Silicon dioxide	USA: NIOSH: TWA	6 mg/m <sup>3</sup>
		USA: OSHA: TWA	20 mppcf
		USA: OSHA: TWA	80 mg/m <sup>3</sup> total dust
1344-28-1	Aluminium oxide	Canada, Alberta: OEL 8 hour	10 mg/m <sup>3</sup>
		Canada, Québec: VEMP	10 mg/m <sup>3</sup> (inhalable fraction)
		USA: OSHA: TWA	15 mg/m <sup>3</sup> inhalable fraction
		USA: OSHA: TWA	5 mg/m <sup>3</sup> (respirable fraction)

### Engineering controls

Provide good ventilation and/or an exhaust system in the work area.  
See also information in chapter 7, section storage.

### Personal protection equipment (PPE)

Eye/face protection	Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010.
Skin protection	Wear suitable protective clothing. Protective gloves according to OSHA Standard - 29 CFR: 1910.138. During splash contact: Glove material: polychloroprene - Layer thickness: > 1 mm Breakthrough time: > 60 min In case of prolonged or frequently repeated skin contact: polychloroprene or natural rubber - Layer thickness: > 1 mm Breakthrough time: > 480 min Observe glove manufacturer's instructions concerning penetrability and breakthrough time.



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

## Essential Glue

Material number 40915000/40916000

Revision date: 12/9/2017

Version: 3

Language: en-CA,US

Date of print: 12/10/2017

Page: 5 of 9

**Respiratory protection:** Respiratory protection must be worn whenever the TLV (WEL) levels have been exceeded. Use filter type P according to OSHA Standard - 29 CFR: 1910.134 or ANSI Z88.2. The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

**General hygiene considerations:**

Do not breathe mist/vapors/spray. Avoid contact with the substance. Avoid contact with skin and eyes.

Contaminated work clothing should not be allowed out of the workplace.

Do not eat, drink or smoke when using this product.

Wash hands before breaks and after work.

## 9. Physical and chemical properties

### Information on basic physical and chemical properties

Appearance:	Physical state at 20 °C and 101.3 kPa: solid Form: pasty Color: white
Odor:	characteristic
Odor threshold:	No data available
pH value:	not applicable
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	No data available
Flash point/flash point range:	Not applicable
Evaporation rate:	No data available
Flammability:	No data available
Explosion limits:	No data available
Vapor pressure:	No data available
Vapor density:	No data available
Density:	1.5 g/cm <sup>3</sup>
Solubility:	No data available
Partition coefficient: n-octanol/water:	No data available
Auto-ignition temperature:	No data available
Thermal decomposition:	No data available
Viscosity, dynamic:	255000 mPa*s

## 10. Stability and reactivity

Reactivity:	Refer to subsection "Possibility of hazardous reactions".
Chemical stability:	Stable under recommended storage conditions.
Possibility of hazardous reactions	No hazardous reaction when handled and stored according to provisions.
Conditions to avoid:	No data available
Incompatible materials:	No data available



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

## Essential Glue

Material number 40915000/40916000

Revision date: 12/9/2017

Version: 3

Language: en-CA,US

Date of print: 12/10/2017

Page: 6 of 9

Hazardous decomposition products:

No hazardous decomposition products when regulations for storage and handling are observed.

Thermal decomposition:

No data available

## 11. Toxicological information

### Toxicological tests

Toxicological effects: The statements are derived from the properties of the single components. No toxicological data is available for the product as such.

Acute toxicity (oral): Based on available data, the classification criteria are not met.  
ATEmix calculated: > 5000 mg/kg

Acute toxicity (dermal): Based on available data, the classification criteria are not met.  
ATEmix calculated: > 5000 mg/kg

Acute toxicity (inhalative): Based on available data, the classification criteria are not met.  
ATEmix calculated (Dusts/mist): > 15 mg/L

Skin corrosion/irritation: Lack of data.

Eye damage/irritation: Lack of data.

Sensitisation to the respiratory tract: Lack of data.

Skin sensitisation: Lack of data.

Germ cell mutagenicity/Genotoxicity: Lack of data.

Carcinogenicity: Lack of data.

Reproductive toxicity: Lack of data.

Effects on or via lactation: Lack of data.

Specific target organ toxicity (single exposure): Lack of data.

Specific target organ toxicity (repeated exposure): Lack of data.

Aspiration hazard: Lack of data.

Other information:

Information about Trimethoxyvinylsilane:

LD50 Rat, oral: 7,120 mg/kg (OECD 401, read across)

LD50 Rabbit, dermal: 3,540 mg/kg

LC50 Rat, inhalative (vapor): 16.8 mg/L/4h (OECD 403, read across)

For carcinogenic effects:

Information about CAS No. 7631-86-9

Carcinogen Status:

IARC Rating: Group 3

OSHA Carcinogen: not listed

NTP Rating: not listed

Information about CAS No. 13463-67-7

Carcinogen Status:

IARC Rating: Group 3

OSHA Carcinogen: not listed

NTP Rating: not listed



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

## Essential Glue

Material number 40915000/40916000

Revision date: 12/9/2017

Version: 3

Language: en-CA,US

Date of print: 12/10/2017

Page: 7 of 9

## 12. Ecological information

### Ecotoxicity

Aquatic toxicity: Information about Trimethoxyvinylsilane:  
Fish toxicity:  
LC50 Oncorhynchus mykiss: 191 mg/L/96h (OECD 203, read across)  
Daphnia toxicity:  
EC50 Daphnia magna (Big water flea): > 100 mg/L/48h (OECD 202, read across)  
Algae toxicity:  
EC50: > 100 mg/L/72h (OECD 201, read across)  
Bacterial toxicity:  
EC50: > 2,500 mg/L/3h (OECD 209, read across)

### Mobility in soil

No data available

### Persistence and degradability

Further details: No data available

### Additional ecological information

Volatile organic compounds (VOC):

0 % by weight

General information: Do not allow to enter into ground-water, surface water or drains.

## 13. Disposal considerations

### Product

Recommendation: Dispose of waste according to applicable legislation.

### Contaminated packaging

Recommendation: Dispose of waste according to applicable legislation. Handle contaminated packages in the same way as the substance itself. Non-contaminated packages may be recycled.

## 14. Transport information

### USA: Department of Transportation (DOT)

Proper shipping name: Not restricted

### Canada: Transportation of Dangerous Goods (TDG)

Shipping name: Not restricted

### Sea transport (IMDG)

Proper shipping name: Not restricted

Marine pollutant: no

### Air transport (IATA)

Proper shipping name: Not restricted



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

## Essential Glue

Material number 40915000/40916000

Revision date: 12/9/2017

Version: 3

Language: en-CA,US

Date of print: 12/10/2017

Page: 8 of 9

### Further information

No dangerous good in sense of these transport regulations.

## 15. Regulatory information

### National regulations - Canada

No data available

### National regulations - U.S. Federal Regulations

Calcium carbonate:	TSCA Inventory: listed TSCA HPVC: not listed
Sulfonic acids, C10-21-alkane, Ph esters:	TSCA Inventory: not listed
Titanium dioxide:	TSCA Inventory: listed TSCA HPVC: not listed Carcinogen Status: IARC Rating: Group 2B OSHA Carcinogen: not listed NTP Rating: not listed NIOSH Recommendations: Occupational Health Guideline: 0617
Trimethoxyvinylsilane:	TSCA Inventory: listed TSCA HPVC: not listed
Silicon dioxide:	TSCA Inventory: listed TSCA HPVC: not listed Carcinogen Status: IARC Rating: Group 3 OSHA Carcinogen: not listed NTP Rating: not listed NIOSH Recommendations: Occupational Health Guideline: 0552
Bis(2,2,6,6-Tetramethyl-4-piperidyl)sebacate:	TSCA Inventory: listed TSCA HPVC: not listed
Aluminium oxide:	TSCA Inventory: listed TSCA HPVC: not listed Other Environmental Laws: SARA Title III Section 313, Toxic Release: Conc. 1.0% / Threshold Standard NIOSH Recommendations: Occupational Health Guideline: 0021



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

## Essential Glue

Material number 40915000/40916000

Revision date: 12/9/2017

Version: 3

Language: en-CA,US

Date of print: 12/10/2017

Page: 9 of 9

### National regulations - U.S. State Regulations

Titanium dioxide: California Proposition 65: cancer  
Rhode Island HSL: listed

Aluminium oxide: Delaware Air Quality Management List:  
DRQ: 100 - RQ State: State requirement differs from Federal  
Massachusetts Haz. Substance codes: F9  
Minnesota Haz. Substance:  
Codes: A - Ratings: 10.16 - Status: Title III, TRI.  
New Jersey RTK Hazardous Substance:  
DOT: - - Sub No.: 2891 - TPQ: -  
Pennsylvania Haz. Substance code: E  
Washington Air Contaminant:  
TWA: 10 mg

### National regulations - EC member states

Customs tariff number: 32141010

## 16. Other information

Hazard rating systems:



NFPA Hazard Rating:

Health: 1 (Slight)

Fire: 1 (Slight)

Reactivity: 1 (Slight)

HMIS Version III Rating:

Health: 1 (Slight)

Flammability: 1 (Slight)

Physical Hazard: 1 (Slight)

Personal Protection: X = Consult your supervisor

HEALTH	1
FLAMMABILITY	1
PHYSICAL HAZARD	1
	X

Reason of change: Changes in section 1: Material number

General revision

Date of first version: 2/5/2017

### Department issuing data sheet

Contact person: see section 1: Dept. responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.