

Essential Glue

Material number 40915000/40916000

Revision date: 9/12/2017 Version: 3 Language: en-UN

Date of print: 10/12/2017

1 of 7

Page:

1. Identification of the substance/mixture and of the company/undertaking

Product identifier

Trade name: Essential Glue

This safety data sheet pertains to the following products:

40915000 40916000

Relevant identified uses of the substance or mixture and uses advised against

General use: Adhesive

Details of the supplier of the safety data sheet

Company name: Grohe AG

Street/POB-No.: Industriepark Edelburg

Postal Code, city: 58675 Hemer

Germany

 WWW:
 www.grohe.com

 E-mail:
 info@grohe.com

 Telephone:
 +49 (0)2372 93-0

 Telefax:
 +49 (0)2372 93-1322

Dept. responsible for information:

Telephone: +49 (0)2372 93-2037 sustainability@grohe.com

Emergency telephone number

GIZ-Nord, Göttingen, Germany, Telephone: +49 551-19240

2. Hazards identification

Classification of the substance or mixture

GHS classification

This mixture is classified as not hazardous.

Label elements

Hazard statements: not applicable Precautionary statements: not applicable

Other hazards

Special danger of slipping by leaking/spilling product.

3. Composition / information on ingredients

Mixtures

Chemical characterisation: Mixture of the substances listed below with non-hazardous additions



Essential Glue

Material number 40915000/40916000

Revision date: 9/12/2017 Version: 3 Language: en-UN

Date of print: 10/12/2017
Page: 2 of 7

Hazardous ingredients:

CAS No.	Designation	Concentration	Classification
CAS 2768-02-7	Trimethoxyvinylsilane	< 3 %	Flammable Liquid 3. Acute Toxicity 4 (inhalative).
CAS 52829-07-9	Bis(2,2,6,6-Tetramethyl-4-piperidyl)sebacate	< 1 %	Eye Damage 1. Aquatic toxicity - acute 1. Aquatic toxicity - chronic 2.

Additional information: Contains: Calcium carbonate, Titanium dioxide, Silicon dioxide, Aluminium oxide: The

maximum workplace exposure limits are, where necessary, listed in section 8.

4. First aid measures

In case of inhalation: Move victim to fresh air. Seek medical treatment in case of troubles.

Following skin contact: Immediately clean with water and soap followed by thorough rinsing. Take off

contaminated clothing and wash it before reuse. In case of skin reactions, consult a

physician.

After eye contact: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids

apart. Remove contact lenses, if present and easy to do. Continue rinsing. In case of

troubles or persistent symptoms, consult an opthalmologist.

After swallowing: Rinse mouth. Never give anything by mouth to an unconscious person.

Do not induce vomiting. Consult doctor afterwards.

Most important symptoms and effects, both acute and delayed

No data available

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

5. Firefighting measures

Extinguishing media

Suitable extinguishing media:

Water fog, foam, extinguishing powder, carbon dioxide.

Extinguishing media which must not be used for safety reasons:

Full water jet

Special hazards arising from the substance or mixture

May form dangerous gases and vapours in case of fire.

In case of fire may be liberated: nitrogen oxides (NOx), carbon monoxide and carbon

dioxide

Advice for firefighters

Special protective equipment for firefighters:

Wear self-contained positive pressure breathing apparatus and full firefighting protective

clothing.

Additional information: Do not allow water used to extinguish fire to enter drains, ground or waterways.



Essential Glue

Material number 40915000/40916000

Revision date: 9/12/2017 Version: en-UN Language: Date of print: 10/12/2017

Page: 3 of 7

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. Avoid contact with the substance. Do not breathe mist/vapours/spray. Avoid contact with skin and eyes. Wear appropriate protective equipment. Take off contaminated clothing and wash it before reuse.

Environmental precautions

Do not allow to enter into ground-water, surface water or drains.

Methods and material for containment and cleaning up

Take up mechanically, placing in appropriate containers for disposal. Thoroughly clean

surrounding area.

Additional information: Special danger of slipping by leaking/spilling product.

7. Handling and storage

Precautions for safe handling

Advices on safe handling: Provide adequate ventilation, and local exhaust as needed. Avoid contact with the substance. Do not breathe mist/vapours/spray. Avoid contact with skin and eyes. Wear appropriate protective equipment. Take off contaminated clothing and wash it before reuse. Do not eat, drink or smoke when using this product. Wash hands before breaks and after work.

Storage

Requirements for storerooms and containers:

Storage temperature: 5 °C up to 25 °C.

Protect from frost. Protect from heat and direct sunlight. Keep container tightly closed in a cool, well-ventilated place.

Hints on joint storage: Do not store together with food.

8. Exposure controls/personal protection

Control parameters

Occupational exposure limit values:

CAS No.	Designation	Туре	Limit value
13463-67-7	Titanium dioxide	USA: ACGIH: TWA	10 mg/m³

Exposure controls

Provide good ventilation and/or an exhaust system in the work area. See also information in chapter 7, section storage.

Personal protection equipment

Occupational exposure controls

Respiratory protection: Respiratory protection must be worn according to AS/NZS 1715 and AS/NZS 1716

whenever the WEL levels have been exceeded.

Use filter type P according to EN 14387.

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.



Essential Glue

Material number 40915000/40916000

Revision date: 9/12/2017 Version: 3 Language: en-UN

Language: en-UN
Date of print: 10/12/2017

4 of 7

Page:

Hand protection: Protective gloves according to AS/NZS 2161.

During splash contact: Glove material: polychloroprene - Layer thickness: > 1 mm

Breakthrough time: > 60 min

In case of prolonged or frequently repeated skin contact: polychloroprene or natural rubber

- Layer thickness: > 1 mm Breakthrough time: > 480 min

Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Eye protection: Tightly sealed eye protectors according to AS/NZS 1337.

Body protection: Wear suitable protective clothing.

General protection and hygiene measures:

Odour:

Odour threshold:

Do not breathe mist/vapours/spray. Avoid contact with the substance. Avoid contact with

skin and eyes.

Contaminated work clothing should not be allowed out of the workplace.

Do not eat, drink or smoke when using this product.

Wash hands before breaks and after work.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance: Physical state at 20 °C and 101.3 kPa: solid

Form: pasty Colour: white characteristic No data available

pH value: not applicable No data available Melting point/freezing point: Initial boiling point and boiling range: No data available Flash point/flash point range: Not applicable Evaporation rate: No data available No data available Flammability: Explosion limits: No data available Vapour pressure: No data available Vapour density: No data available

Density: 1.5 g/cm³

Solubility: No data available
Partition coefficient: n-octanol/water: No data available
Auto-ignition temperature: No data available
Thermal decomposition: No data available

Additional information

Viscosity, dynamic: 255000 mPa*s

10. Stability and reactivity

Reactivity: Refer to 10.3

Chemical stability: Stable under recommended storage conditions.



Essential Glue

Material number 40915000/40916000

Revision date: 9/12/2017 Version: 3 Language: en-UN Date of print: 10/12/2017

Page: 5 of 7

Possibility of hazardous reactions:

No hazardous reaction when handled and stored according to provisions.

Conditions to avoid: No data available

Incompatible materials: No data available

Hazardous decomposition products:

No hazardous decomposition products when regulations for storage and handling are

observed.

Thermal decomposition: No data available

11. Toxicological information

Information on toxicological effects

Toxicological effects: The statements are de

The statements are derived from the properties of the single components. No toxicological

data is available for the product as such.

Acute toxicity (oral): Based on available data, the classification criteria are not met.

ATEmix calculated: > 5000 mg/kg

Acute toxicity (dermal): Based on available data, the classification criteria are not met.

ATEmix calculated: > 5000 mg/kg

Acute toxicity (inhalative): Based on available data, the classification criteria are not met.

ATEmix calculated (Dusts/mist): > 15 mg/L

Skin corrosion/irritation: Lack of data. Eye damage/irritation: Lack of data.

Sensitisation to the respiratory tract: Lack of data.

Skin sensitisation: Lack of data.

Germ cell mutagenicity/Genotoxicity: Lack of data.

Carcinogenicity: Lack of data.

Reproductive toxicity: Lack of data.

Effects on or via lactation: Lack of data.

Specific target organ toxicity (single exposure): Lack of data. Specific target organ toxicity (repeated exposure): Lack of data.

Aspiration hazard: Lack of data.



Essential Glue

Language: Date of print: 10/12/2017 Material number 40915000/40916000 Page: 6 of 7

Revision date: 9/12/2017

Version:

Information about Trimethoxyvinylsilane: Other information:

LD50 Rat, oral: 7,120 mg/kg (OECD 401, read across)

LD50 Rabbit, dermal: 3,540 mg/kg

LC50 Rat, inhalative (vapour): 16.8 mg/L/4h (OECD 403, read across)

For carcinogenic effects:

Information about CAS No. 7631-86-9

Carcinogen Status: IARC Rating: Group 3

OSHA Carcinogen: not listed

NTP Rating: not listed

Information about CAS No. 13463-67-7

Carcinogen Status: IARC Rating: Group 3

OSHA Carcinogen: not listed

NTP Rating: not listed

12. Ecological information

Toxicity

Aquatic toxicity: Information about Trimethoxyvinylsilane:

Fish toxicity:

LC50 Oncorhynchus mykiss: 191 mg/L/96h (OECD 203, read across)

Daphnia toxicity:

EC50 Daphnia magna (Big water flea): > 100 mg/L/48h (OECD 202, read across)

Algae toxicity:

EC50: > 100 mg/L/72h (OECD 201, read across)

Bacterial toxicity:

EC50: > 2,500 mg/L/3h (OECD 209, read across)

Persistence and degradability

Further details: No data available

Mobility in soil

No data available

Additional ecological information

General information: Do not allow to enter into ground-water, surface water or drains.

13. Disposal considerations

Waste treatment methods

Product

Recommendation: Dispose of waste according to applicable legislation.

Contaminated packaging

Recommendation: Dispose of waste according to applicable legislation. Handle contaminated packages in

the same way as the substance itself. Non-contaminated packages may be recycled.



Essential Glue

Material number 40915000/40916000

Revision date: 9/12/2017 Version: 3 Language: en-UN

Date of print: 10/12/2017
Page: 7 of 7

14. Transport information

UN number

ADR/RID, IMDG, IATA-DGR:

not applicable

Land transport (ADR/RID)

Product designation: Not restricted

Sea transport (IMDG)

Proper shipping name: Not restricted

Marine pollutant:

Air transport (IATA)

Proper shipping name: Not restricted

Further information

No dangerous good in sense of these transport regulations.

15. Regulatory information

Further regulations, limitations and legal requirements

No data available

16. Other information

Reason of change: Changes in section 1: Material number

General revision

Date of first version: 5/2/2017

Department issuing data sheet

Contact person: see section 1: Dept. responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.